







RoHS 客户图

目錄 MAPX	變更內容 MODIFICATION	日期 DATE
A0	NEW	09-10-20



RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

- NOTE:
- MATERIAL SPECIFICATION:
 - HOUSING: HIGH TEMPERATURE RESISTANT PLASTIC, UL94 V-0.
 - CONTACTS: COPPER ALLOY
 - MID PLATE: STAINLESS STEEL
 - FRONT SHELL: STAINLESS STEEL
 - PLATING SPECIFICATION:
 - 2-1. CONTACTS: Ni 50μ" MIN. UNDER PLATED OVER ALL.
 - 2-2. FRONT SHELL: Au PLATED ON THE FUNCTIONAL AREA OF CONTACT. (GOLD PLATING THICKNESS FOLLOW THE P/N) PLATING SPECIFICATIONS OF THE SOLDER AREA FOLLOW THE P/N SEE TABLE1.
 - 2-3. SHIELD PLATE&MID PLATE: CLEAR ONLY
 - MECHANICAL PERFORMANCE:
 - 3-1. INSERTION FORCE: 0.5~2.0kgf.
 - 3-2. REMOVAL FORCE: 0.8kgf~2.0kgf.
 - 3-3. DURABILITY: 5000 CYCLES.
 - ELECTRICAL PERFORMANCE:
 - 4-1. CURRENT RATING: 3.0A VOLTAGE RATING: 5.0V
 - 4-2. LOCK: YES & GND PINS AND OTHER PINS: 40mΩ/PIN MAX. SHIELD: 50mΩ/MAX. SOLDER MAX. CHANGE OF ALL PINS: 10mΩ.
 - 4-3. INSULATION RESISTANCE: 100MΩ MIN
 - 4-4. DIELECTRIC WITHSTAND VOLTAGE, AC 100V FOR 1 MINUTE.
 - ENVIRONMENTAL PERFORMANCE:
 5. OPERATING TEMPERATURE: -25° C~+85° C.
 6. IR REFLOW: THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260° C.

PRODUCT CHART DWG

PIN ASSIGNMENT S			
A9	VBUS	B12	GND
A12	GND	B9	VBUS
P1N	SIGNAL NAME	P1N	SIGNAL NAME
L	L-6, 5	H	H-0, 9
L-6, 8	H	H-1, 5	

产品图		深圳市鑫风雷电子有限公司	
公差一览表 TOLERANCE UNLESS OTHERWISE		Shenzhen xinfenglei Electronic Co., Ltd	
X	±0.30	MM	王冠
X	±0.25	MM	雷永健
XX	±0.30	MM	雷永健
XXX	±0.15	MM	雷永健
单位 UNITS	MM	制图 DRAWING	王冠
比例 SCALE	1:1	审核 CHECK	雷永健
日期 DATE	2009/10/20	核准 APPRO	雷永健
产品料号 PRODUCT PART NO.	00305-UCAF007-X	产品名称 PRODUCT NO.	TYPE C 4P 180度插板DIP
角法 VIEW	角法 VIEW	版本 VER	A0