








1 2 3 4 5 6 7 8 9 10

RoHS 客户图



RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

PIN ASSIGNMENTS

A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2
PIN	SIGNAL NAME	PIN	SIGNAL NAME

目錄 MAPX	變更內容 MODIFICATION	日期 DATE
A0	NEW	09-10-20

NOTE:

- 1.MATERIAL SPECIFICATION:
1.HOUSING:HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0.
 - 2.CONTACTS:COOPER ALLOY
 - 3.MID PLATE: STAINLESS STEEL
 - 4.FRONT SHELL: STAINLESS STEEL
- 2.PLATING SPECIFICATION:
2-1.CONTACTS:
IN 50u" MIN. UNDER PLATED OVER ALL.
AU PLATED ON THE FUNCTIONAL AREA OF CONTACT.
(GOLD PLATING THICKNESS FOLLOW THE P/N)
PLATING SPECIFICATIONS OF THE SOLDER AREA FOLLOW THE P/N
2-2.FRONT SHELL:
SEE TABLE1.

- 2-3.SHIELD PLATE&MID PLATE:
CLEAR ONLY

- 3.MECHANICAL PERFORMANCE:
3-1.INSERTION FORCE: 0.5~2.0kgf.
3-2.REMOVAL FORCE: 0.8kgf~2.0kgf.
3-3.DURABILITY: 5000 CYCLES.
- 4.ELECTRICAL PERFORMANCE:
4-1. CURRENT RATING:3.0A
VOLTAGE RATING:5.0V

- 4-2. LCR:
VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX.
SHIELD: 50mΩ/MAX.
LCR MAX. CHANGE OF ALL PINS: 10mΩ.
4-3.INSULATION RESISTANCE: 100MΩ MIN
4-4.DIELECTRIC WITHSTAND VOLTAGE:AC 100V FOR 1 MINUTE.
5. ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -25℃~+85℃.
- 6.IR REFLOW:
THE PEAK TEMPERATURE ON THE BOARD SHALL
BE MAINTAINED FOR 10 SECONDS AT 260℃.

产品图

PRODUCT CHART DWG

深圳市鑫风雷电子有限公司

Shenzhen xinfenglei Electronic Co., Ltd

公差一览表

公差一览表	单位 UNITS	比例 SCALE	日期 DATE	制图 DRAWING	产品料号 PRODUCT PART NO.
TOLERANCE UNLESS OTHERWISE				王冠	00723-UCAF013-X
X. ±0.30	X'. ±5°	I:1	2009/10/20	审核	产品名称
.X. ±0.25	.X'. ±2°			雷永健	TYPE C 6P 180度SMT脚长0.9 H=7.4
.XX ±0.30	.XX' ±1°			核准	角法
.XXX ±0.15	.XXX' ±0.5°			雷永健	版本
				APPD	VER
					A0