


1. ELECTRICAL CHARACTERISTICS:
 - 1-1. CONTACT RESISTANCE: 30m MAX. Ω
 - 1-2. DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR ONE MINUTE.
 - 1-3. INSULATION RESISTANCE: 100M MIN. MEASURED BY 500 VDC.
2. MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE : 0.5-2.0Nf (BER.)
 - 2-2. WITHDRAWAL FORCE : 0.8-2.0Nf (BER.)
3. LIFE TEST: 10,000 CYCLES.

RECOMMENDED P.C.B. LAYOUT (1:1.00mm)
TOLERANCE UNSPECIFIED ±0.05mm



VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010
VI	010	B12	010

公差一覽表 TOLERANCE UNLESS OTHERWISE	公差一覽表 TOLERANCE UNLESS OTHERWISE	公差一覽表 TOLERANCE UNLESS OTHERWISE	公差一覽表 TOLERANCE UNLESS OTHERWISE
X	±0.30	X	±5°
.X	±0.25	.X	±2°
.XX	±0.20	.XX	±1°
.XXX	±0.15	.XXX	±0.5°

产品图

深圳市鑫风雷电子有限公司

单位	MM	制图	王冠	产品料号	01002-UCAF025-X
比例	1 : 1	审核	雷永健	产品名称	TYPE C 16P-标准180度DIP H=10.0
日期	2009/10/20	核准	雷永健	图法	VER
				版本	A0