






1 2 3 4 5 6 7 8 9 10

Rohs 客户图



PCB LAYOUT



— PRODUCT SPECIFICATION

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
d. OPERATING TEMPERATURE: -55° C~ 85° C
e. MATING FORCE:35N MAX; UNMATING FORCE:10N MIN

— .PRODUCT SPECIFICATION

2. 1. CONTACT RESISTANCE: 30 MILLIOHMS MAX
2. 2. DIELECTRIC WITHSTANDING VOLTAGE: AC 500/300 V Min (UNMATED /MATED)
2. 3. INSULATION RESISTANCE: 100/10 MΩ Min (UNMATED /MATED)
2. 4. MATING FORCE:44. 1N MAX; UNMATING FORCE:9. 8~39. 2N
2. 5. DURABILITY:1500 CYCLES

三. ALL MATERIALS MEET THE ROHS REQUIREMENT

HDMI PIN MAP

1. TMDS DATA 2+	2. TMDS DATA2 SHIELD
3. TMDS DATA 2-	4. TMDS DATA 1+
5. TMDS DATA 1 SHIELD	6. TMDS DATA 1-
7. TMDS DATA 0+	8. TMDS DATA 0 SHIELD
9. TMDS DATA 0-	10. TMDS CLOCK+
11. TMDS CLOCK SHIELD	12. TMDS CLOCK-
13. CEC	14. NO CONNECTED
15. DDC CLOCK	16. DDC DATA
17. GROUND	18. +5V POWER
19. HOT PLUG DETECT	

USB PIN MAP

Contact Number	Signal Name	Typical Wiring Assignment
1	VBUS	Red
2	D-	White
3	D+	Green
4	GND	Black

PART NO: 8005F-2000011-X


SERISE:Multilayer

Receptacle

serial number

Variable

NO.	PART NAME	MATERIAL	PLATING
1	HOUSING-A	LCP+30%GF BK	
2	HOUSING-B	LCP+30%GF BK	
3	CONTACT-A	C5191 T=0.2	Au/Sn
4	CONTACT-B	C5191 T=0.25	Au/Sn
5	SHELL-A	SPCC T=0.3	NI
6	SHELL-B	SPCC T=0.3	NI
5	SHELL-C	SPCC T=0.5	NI
6	SHELL-D	SPCC T=0.3	NI



产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

单位	MM	制图	王冠	产品料号	8005F-2000011-X
比例	1:1	审核	雷永健	产品名称	双层 USB2.0+HDMI A TYPE B=18.00 L=20.60
日期	2009/10/20	核准	雷永健	联系方式	mailto:sale1@xfll.com
DATE		Appd	Lei Yong Jian	Lei Yong Jian	www.xfll.com.cn

深圳市鑫风雷电子有限公司
Shenzhen xinfenglei Electronics Co., Ltd

目錄
MAPX

设变内容
MODIFICATION

日期
DATE

A0

NEW

09-10-20