

1

2

3

4

5

6

7

8

9

10

RoHS

客户图

目錄

MAPX

MODIFICATION

日期
DATE

A0

NEW

09-10-20

卡勾材质: C2680

胶芯材质: LCP

端子材质: C2680 电镀1U

PIN ASSIGNMENTS:

PIN NUMBER	SIGNAL NAME
PIN 1#	DETECT1
PIN 2#	GND
PIN 3#	DP1
PIN 4#	DN1
PIN 5#	ACC1
PIN 6#	FWR1N
PIN 7#	DN2
PIN 8#	DP2
PIN 9#	ACC2
PIN 10#	DETECT2
SHELL	GND

NOTES:

SPECIFICATION:

1. CURRENT RATING: 3.0A MAX
2. VOLTAGE: 100 VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. INSERTION FORCE : 5N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY: 500 CYCLES

PART NO: 8017F-1000002-X

SERISE: TYPE C

Receptacle

serial number

Variable

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE	UNIT	制图	王冠	产品料号	8017F-1000002-X
X ±0.30	X'	±5'	雷永健	产品名称	S100苹果 10P双面母座夹板1.25厚 L=11.1
.X ±0.25	.X'	±2'	审核	PRODUCT NO.	mailbox: sale1@xfll.com
.XX ±0.20	.XX'	±1'	批准	联系方式	www.xfll.com.com
.XXX ±0.15	.XXX'	±0.5'	日期	2009/10/20	

深圳市鑫风雷电子有限公司

Shenzhen xinfenglei Electronics Co., Ltd