









# RoHS 客户图



A1	GN0	B12	GN0
A2		B11	
A3	VBIS	B10	VBIS
A4	VBIS	B9	VBIS
A5	CC1	B8	SB02
A6	DP1	B7	DP2
A7	DN1	B6	DN2
A8	SB01	B5	CS
A9	VBIS	B4	VBIS
A10		B3	
A11		B2	
A12	GN0	B1	GN0

RECOMMENDED P.C.B. LAYOUT  
TOLERANCE UNSPECIFIED ±0.05mm



目錄 MAPX	变更内容 MODIFICATION	日期 DATE
A0	NEW	09-10-20

- NOTE:  
备注:
- MATERIAL SPECIFICATION:
  - 材料规格:
  - 1-1. HOUSING: HIGH TEMPERATURE RESISTANT PLASTIC. UL94 V-0.
  - 1-1. 外壳材料: 高温塑胶, 防火等级UL94 V-0.
  - 1-2. TERMINAL: COPPER ALLOY
  - 1-2. 端子材料: 铜合金
  - 1-3. FRONT SHELL: STAINLESS STEEL
  - 1-3. 外壳材料: 不锈钢
  - 1-4. MID PLATE: STAINLESS STEEL
  - 1-4. 中夹片: 不锈钢
  2. PLATING SPECIFICATION:
  2. 电镀规格:
  - 2-1. TERMINAL:
  - 2-1. 端子: Ni, 30u" MIN., UNDER PLATED OVER ALL.
  - 镀镍层 30u" MIN.
  - Au PLATED Golden Flash OVER NI
  - 表面镀金 Golden Flash
  - 2-2. FRONT SHELL:
  - 2-2. 外壳: Ni, 30u" MIN., PLATED OVER ALL.
  - 镍层 30u" MIN.
  - 2-3. MECHANICAL PERFORMANCE:
  - 2-3. 机械性能: 3. 1. INSERTION FORCE: 0.5~2.0kgf.
  - 3-1. 插入力: 0.5~2.0kgf.
  - 3-2. REMOVAL FORCE: 0.6kgf~2.0kgf.
  - 3-2. 拔出力: 0.6kgf~2.0kgf.
  - 3-3. DURABILITY: 10000 CYCLES.
  - 3-3. 插拔寿命: 10000次.
  4. ELECTRICAL PERFORMANCE:
  4. 电气性能:
  - 4-1. VOLTAGE RATING: 48V DC/AC
  - 4-1. 额定电压: 48V DC/AC
  - 4-2. CURRENT RATING: 5A
  - 4-2. 额定电流: 5.0A
  - 4-3. ILCR: 50mΩ/PIN MAX.
  - 4-3. 接触电阻: 50mΩ/PIN MAX.
  - 4-4. INSULATION RESISTANCE: 100MΩ MIN
  - 4-4. 绝缘电阻: 100MΩ MIN
  - 4-5. DIELECTRIC WITHSTAND VOLTAGE: AC 100V FOR 1 MINUTE.
  - 4-5. 耐压: AC 100V FOR 1 MINUTE.
  5. ENVIRONMENTAL PERFORMANCE:
  5. 环境特性:
  - 5-1. OPERATING TEMPERATURE: -25°C~+85°C.
  - 5-1. 工作温度: -25°C~+85°C.

PART NO.: 8001F-FS16017-C

SERIE: TYPE IC  
Receptacle  
serial number  
Variable

产品图  
PRODUCT CHART DWG  
深圳市鑫风雷电子有限公司  
Shenzhen xinfenglei Electronic Co., Ltd

公差一览表 TOLERANCE UNLESS OTHERWISE	单位 UNITS	MM	制图 DRAWING	王冠	产品料号 PRODUCT PART NO.	8001F-FS16017-C
X	±0.30	X'	±5'	审核 CHECK	产品名称 PRODUCT NO.	TYPE C 18P母座180度插板 H=7.6 防水型 两脚
.XX	±0.25	.X'	±2'	核准 APPR	版本 VER	A0
.XXX	±0.30	.XX'	±1'	日期 DATE	2009/10/20	
	±0.15	.XXX'	±0.5'			